

4 Combination table

4 - 1 Combination Table

2MXM40A9

Cooling ·230V 50Hz·

Outdoor unit	Indoor unit	Cooling capacity [kW]		Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room ·A·	Room ·B·	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
2MXM40M2V1B 2MXM40M3V1B 2MXM40M4V1B 2MXM40N2V1B 2MXM40N2V1B9 2MXM40A2V1B 2MXM40A2V1B9	1.5	1,50	-	1,30	1,50	2,00	0,33	0,31	0,40	1,78	1,70	2,17	79
	2.0	2,00	-	1,30	2,00	2,40	0,33	0,44	0,57	1,78	2,38	3,09	79
	2.5	2,50	-	1,30	2,50	3,00	0,33	0,61	0,80	1,78	3,33	4,40	79
	3.5	3,50	-	1,30	3,50	4,00	0,33	1,04	1,35	1,78	5,71	7,38	79
	1.5+1.5	1,50	1,50	1,50	3,00	3,60	0,31	0,60	0,73	1,67	3,33	4,00	79
	1.5+2.0	1,50	2,00	1,50	3,50	4,00	0,31	0,79	0,91	1,67	4,35	4,98	79
	1.5+2.5	1,50	2,50	1,50	4,00	4,20	0,31	0,98	1,03	1,67	5,37	5,64	79
	1.5+3.5	1,20	2,80	1,50	4,00	4,40	0,31	0,96	1,06	1,67	5,30	5,83	79
	2.0+2.0	2,00	2,00	1,50	4,00	4,20	0,31	0,97	1,02	1,67	5,34	5,61	79
	2.0+2.5	1,78	2,22	1,50	4,00	4,30	0,31	0,96	1,04	1,67	5,30	5,70	79
	2.0+3.5	1,45	2,55	1,50	4,00	4,50	0,31	0,95	1,08	1,67	5,25	5,91	79
	2.5+2.5	2,00	2,00	1,50	4,00	4,40	0,31	0,96	1,06	1,67	5,27	5,80	79
	2.5+3.5	1,67	2,33	1,50	4,00	4,60	0,31	0,94	1,09	1,67	5,20	5,98	79

Notes

- 1) The total capacity of each connected indoor unit is up to ·6·kW.
- 2) The values mentioned in this document are for connecting with the following indoor unit types:
·1.5, 2.0, 2.5, 3.5· kW class
Wall-mounted ·CTXA-AS, CTXA-AT, CTXA-AW, CTXA-BB, CTXA-BS, CTXA-BT, CTXM-M, CTXM-N, CTXM-R, FTXA-AS, FTXA-AT, FTXA-AW, FTXA-BB, FTXA-BS, FTXA-BT, FTXM-M, FTXM-N, FTXM-R, FTJX-AB, FTJX-AS, FTJX-AW· series
- 3) Cooling capacity conditions
Indoor temperature ·27·°C DB / ·19·°C WB
Outdoor temperature ·35·°C DB
- 4) For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see ·3D106169·.

4D139784B

2MXM40A9

Heating ·230V 50Hz·

Outdoor unit	Indoor unit	Heating capacity [kW]		Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room ·A·	Room ·B·	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
2MXM40M2V1B 2MXM40M3V1B 2MXM40M4V1B 2MXM40N2V1B 2MXM40N2V1B9 2MXM40A2V1B 2MXM40A2V1B9	1.5	2,00	-	1,00	2,00	3,30	0,26	0,68	1,04	1,43	3,66	5,69	79
	2.0	2,70	-	1,00	2,70	3,70	0,26	0,75	1,24	1,43	4,11	6,78	79
	2.5	3,40	-	1,00	3,40	4,10	0,26	1,02	1,48	1,43	5,59	8,09	79
	3.5	3,80	-	1,00	3,80	4,40	0,26	1,28	1,71	1,43	7,02	9,40	79
	1.5+1.5	1,75	1,75	1,20	3,50	4,30	0,24	0,80	0,99	1,31	4,43	5,45	79
	1.5+2.0	1,63	2,17	1,20	3,80	4,50	0,24	0,88	1,04	1,31	4,85	5,75	79
	1.5+2.5	1,58	2,63	1,20	4,20	4,60	0,24	1,00	1,10	1,31	5,53	6,06	79
	1.5+3.5	1,26	2,94	1,20	4,20	4,70	0,24	0,96	1,12	1,31	5,29	5,92	79
	2.0+2.0	2,10	2,10	1,20	4,20	4,60	0,22	0,98	1,08	1,21	5,41	5,93	79
	2.0+2.5	1,87	2,33	1,20	4,20	4,70	0,22	0,97	1,09	1,21	5,36	6,00	79
	2.0+3.5	1,53	2,67	1,20	4,20	4,80	0,22	0,95	1,09	1,21	5,25	6,00	79
	2.5+2.5	2,10	2,10	1,20	4,20	4,70	0,22	0,96	1,08	1,21	5,29	5,92	79
	2.5+3.5	1,75	2,45	1,20	4,20	4,80	0,22	0,94	1,08	1,21	5,19	5,94	79

Notes

- 1) The total capacity of each connected indoor unit is up to ·6·kW.
- 2) The values mentioned in this document are for connecting with the following indoor unit types:
·1.5, 2.0, 2.5, 3.5· kW class
Wall-mounted ·CTXA-AS, CTXA-AT, CTXA-AW, CTXA-BB, CTXA-BS, CTXA-BT, CTXM-M, CTXM-N, CTXM-R, FTXA-AS, FTXA-AT, FTXA-AW, FTXA-BB, FTXA-BS, FTXA-BT, FTXM-M, FTXM-N, FTXM-R, FTJX-AB, FTJX-AS, FTJX-AW· series
- 3) Heating capacity conditions
Indoor temperature ·20·°C DB
Outdoor temperature ·7·°C DB / ·6·°C WB
- 4) For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see ·3D106169·.

4D139786B