



Simplified remote controller

Compatible with Sky Air and VRV

BRC2E52C / BRC3E52C



Daikin's simplified remote controller range offers a hard wired remote option for applications that require restricted functionality of the remote – for example, hotel rooms

Functionality

The simplified remote (BRC2E52C) allows access to:

- > On/Off
- > Temperature Up/Down
- > Fan Speed
- > Mode (heat / cool)

The BRC3E52 version does not have the Mode button and is recommended for heat recovery systems.

While supplied 'locked', allowing access only to the functions listed above, the simplified remote is able to be unlocked as part of commissioning, allowing access to field codes, schedules or energy saving features.

Stylish fascia option

Both BRC2E52 and BRC3E52 options are available with the stylish option, with a choice of finishes:

- > Brushed chrome
- > Polished chrome
- > Polished brass

The stylish option is designed to be recessed into the wall, with the push-fit fascia plate secured without need for screws.

Compatibility

All simplified remote are compatible with Sky Air and VRV indoor units.



BRC2E52C simplified remote – with Mode button



BRC3E52C simplified remote – without Mode button



Brushed Chrome Stylish option for BRC2E52C simplified remote

BRC2E52C / BRC3E52C

Features	Benefits
Simplified control	Makes operating the air conditioning straight forward with access only to temperature up/down, fan-speed and mode
Stylish fascia options	Choice of brushed chrome, polished chrome or polished brass finishes to suit room style
Setback	Maintains the room temperature between upper and lower limits, even when room is unoccupied or system is turned off. Setback can be turned off via service menu
Access to service menus	By unlocking the controller, access can be allowed to Energy saving Functions, timer schedules and service menus. This can help during commissioning to ensure system is set up correctly – then locked afterwards to re-instate 'simple' control
Key card interface	Simplified remote can be connected, via optional BRP7A51 adaptor, to a hotel room key card adaptor and /or window contact. The interface can set delays on the air conditioning turning off, or re-instate original settings, after a key-card is removed

Simplified remote dimensions (surface mounted)

BRC2E52C / BRC3E52C	Height: 120mm	Width: 120mm	Depth: 19mm
----------------------------	---------------	--------------	-------------

Stylish option dimensions (recessed)

Fascia	Height: 142mm	Width: 152mm	Depth: 3mm
Backbox	Height: 135.1mm	Width: 145.4mm	Depth: 36.2mm



Stylish remote without fascia fitted



Stylish remote with brushed chrome fascia fitted

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com