



## FTXP-N(9) / RXP-N(8/9) comfora



## Compact Wall Mount

Experience impressive performance and near-silent operation with Daikin Comfora — designed to fit seamlessly into any space with its minimal footprint.

Perfect for bedrooms thanks to its whisper-quiet night mode, and ideal for living areas with its sleek, space-saving design, Comfora brings comfort, clean air, and effortless control right to your fingertips — all while helping reduce your energy use.

### **Daikin Onecta App**

Control your air conditioning with your phone through Daikin's own Onecta App. Available on Apple and Android, control your system with ease, from anywhere. Enjoy easy voice control of your units by connecting Onecta to Google Home or Amazon Alexa.

### **Smart energy saving**

With Econo Mode, you can lower your air conditioner's power consumption and free up energy for other home appliances — ideal for efficient, everyday living. Better still, Comfora uses just 1 watt in standby mode, helping you save energy even when it's not in use.

### **Quieter than a whisper**

With Silent mode enabled via the remote, the indoor unit reduces its sound level by 3 dB(A) — dropping from around 22–25 dB(A) to as low as 19 dB(A). That's quieter than a soft whisper or rustling leaves, making it ideal for restful sleep, watching TV, or reading in peace.

### **Breathe cleaner, live better**

Daikin Comfora helps create a healthier home environment by combining a Titanium Apatite filter to neutralise unwanted odours with a Silver Allergen filter that captures pollen and airborne particles — ideal for allergy sufferers and fresh indoor living all year round.

### **Designed for restful sleep**

Night Set Mode dims display lights, lowers sound, and softens airflow — perfect for light sleepers and peaceful nights without disturbance.



ARC480A78 (class 20-50)  
ARC480A53 (class 60-71)



RXP20-35N9



BRC073  
(optional)



WI-FI ADAPTOR

INCLUDED AS STANDARD



Indoor Units			FTXP20N9	FTXP25N9	FTXP35N9	FTXP50N9	FTXP60N	FTXP71N
Capacity	UK Total Cooling	kW	1.95	2.44	3.42	4.89	5.86	6.93
	UK Sensible Cooling	kW	1.69	1.94	2.49	3.42	4.00	4.73
	Nominal Cooling	kW	2.0	2.5	3.5	5.0	6.0	7.1
	Nominal Heating	kW	2.5	3.0	4.0	6.0	7.0	8.2
Seasonal Efficiency (EN14825) COOLING	Energy Label		A++	A++	A++	A++	A++	A++
	Pdesign	kW	2.0	2.5	3.5	5.0	6.0	7.1
	SEER		7.20	7.20	7.20	7.10	6.82	6.20
	Annual Energy Consumption kWh		97	121	170	246	308	401
Seasonal Efficiency (EN14825) HEATING	Energy Label		A++	A++	A++	A+	A+	A+
	Pdesign	kW	2.2	2.4	2.8	4.6	4.8	6.2
	SCOP		4.65	4.61	4.64	4.34	4.10	4.01
	Annual Energy Consumption kWh		663	728	845	1498	1638	2166
Air Flow Rate (Cooling)	High / Med / Low / Silent	m³/min	9.6 / 7.5 / 5.6 / 4.4	9.9 / 7.5 / 5.8 / 4.4	11.5 / 8.3 / 6.3 / 4.5	16.3 / 14.0 / 11.5 / 8.3	16.8 / 14.4 / 11.8 / 9.2	16.8 / 14.4 / 11.8 / 10.1
Dimensions	Height	mm	286	286	286	286	295	295
	Width	mm	770	770	770	770	990	990
	Depth	mm	225	225	225	225	263	263
Weight		kg	8.5	8.5	9	9	13.5	13.5
RAL Colour			RAL 9002	RAL 9002	RAL 9002	RAL 9002	RAL 9002	RAL 9002
Sound Pressure (Cooling)	High / Med / Low / Silent	dBA	39 / 33 / 25 / 19	40 / 33 / 26 / 19	43 / 34 / 27 / 20	43 / 39 / 34 / 27	45 / 41 / 36 / 30	46 / 42 / 37 / 32
Sound Pressure (Heating)	High / Med / Low / Silent	dBA	39 / 34 / 28 / 21	40 / 34 / 28 / 21	40 / 35 / 29 / 21	42 / 38 / 33 / 30	44 / 40 / 35 / 32	45 / 41 / 36 / 33
Sound Power (Cooling)		dBA	55	55	58	59	60	62
Outdoor Units			RXP20N9	RXP25N9	RXP35N9	RXP50N8	RXP60N9	RXP71N9
Dimensions	Height x Width x Depth	mm	556 x 740 x 343	556 x 740 x 343	556 x 740 x 343	610 x 923 x 367	734 x 954 x 401	734 x 954 x 401
Weight		kg	24	24	24	40	50	50
Electrical Details	Power Supply	1ph	1ph	1ph	1ph	1ph	1ph	1ph
	Maximum Input Current (MCA)	A	7.99	7.99	9.20	11.81	15.70	15.70
	Max Fuse Size	A	16	16	16	13	16	16
	Interconnection Wiring	Core / Cable Size	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5
Piping Connections	Liquid / Gas	inches (mm)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 1/2 (12.7)	1/4 (6.4) / 1/2 (12.7)	1/4 (6.4) / 1/2 (12.7)
	Pipework	Maximum Length	m	20	20	20	30	30
		Maximum Vertical Rise	m	12	12	12	20	20
		Precharged to	m	10	10	10	10	10
Sound Pressure (Cooling)	Additional charge	g/m	20	20	20	20	20	20
	Holding charge	kg	0.55	0.55	0.70	0.90	1.15	1.15
	Nominal	dBA	46	46	48	47	49	52
	Nominal	dBA	47	47	48	49	49	52
Sound Power (Cooling)	Sound Power (Cooling)	dBA	61	61	62	61	63	66
	Operating Range (Cooling) Min / Max	°CDB	-10 / 48	-10 / 48	-10 / 48	-10 / 48	-10 / 48	-10 / 48
	Operating Range (Heating) Min / Max	°CWB	-15 / 18	-15 / 18	-15 / 18	-15 / 18	-15 / 18	-15 / 18
	Air Flow Rate (Cooling)	Nominal	m³/min	27.6	27.6	28.2	41.0	45.5
Meets ETL criteria			●	●	●	●		

### Accessories:

Accessory Ref	Description
BRC073*	Wired remote control – connection cable required – needs KRP980A1 for class 20-50
KRP980A1	PCB Interface adaptor required for BRC073 (only sizes 2.0kw, 2.5kw, 3.5kw & 5.0kW)
BRCW901A03	3m extension cord required for wired remote controller BRC073
BRCW901A08	8m extension cord required for wired remote controller BRC073
K.CWB90-2	Wall bracket (90kg, 500mm support arm)
K.DT1	Condensate drip tray for use with K.CWB90-2
K.FF600S	Two flexi-feet (Standard 600mm x 185mm x 100mm) to mount the outdoor unit
K.CGS	Condensing unit guard (750 x 1050 x 460)
K.CGM	Condensing unit guard (1150 x 1150 x 650)
KLIC-DDV3*	KNX interface for Split type systems
KRP413A1S	Adaptor PCB for remote on/off control – constant/pulse contact
KRP928A2S*	Adaptor PCB for interface to Daikin centralised control systems
RTD-RA*	Adaptor PCB for Modbus connection and/or extended system functions

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.

### Notes & Features:

- Class 20-50 fan coils are supplied with IR remote controller ARC480A78; class 60&71 fan coils use IR remote controller ARC480A53
- Wifi adaptor included as standard
- Whisper quiet in operation down to 19 dBA with 'Silent Mode' operation
- The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation
- Space saving contemporary wall mounted design
- Can be connected to MXM & MWXM multi split systems (sizes 20-35)



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)

