



## FTXA-C (W/S/B) / RXA-A/B (8) *stylish*



# Stylish

## Where innovation meets creativity

With its sleek white, black, or silver finish, this compact unit blends effortlessly into any interior. Advanced airflow technology and an intelligent thermal sensor ensure a perfectly balanced climate throughout the room, while near-silent operation keeps your space calm and undisturbed. And with Daikin's Flash Streamer technology, the air you breathe stays fresh, clean, and allergen-free — so you can relax, focus, or entertain in total comfort.

### Refined design, effortlessly elegant

Crafted to suit the most stylish interiors, this unit combines sleek form with smart function. With a depth of less than 19 cm and a choice of white, black, or silver finishes, it blends seamlessly into any décor — whether in a sophisticated home or a high-end boutique. Its compact presence never intrudes, making it ideal for those who value both space and aesthetic harmony.

### Subtle airflow, complete comfort

Thanks to the Coanda effect, airflow is gently guided along ceilings or walls, creating a soft, natural climate throughout the room. This ensures even temperature distribution, eliminating drafts and creating a space that feels consistently pleasant — whether you're hosting friends, unwinding at home, or welcoming customers into a serene setting.

### Comfort that senses your needs

An intelligent thermal sensor reads the room's surface temperatures and intuitively adjusts the airflow to match. It begins by evenly spreading air throughout the space, then shifts to target specific zones that need heating or cooling. The result? A perfectly balanced environment that feels tailored to your daily rhythms — without you lifting a finger.

### Breathe well, live well

Daikin's Flash Streamer technology purifies your air continuously, breaking down allergens and odours at a molecular level. Whether it's pollen, pet dander, or lingering smells, the result is a fresher, cleaner space where you can breathe freely — ideal for homes focused on wellness and shops that care about customer comfort.

### Daikin Onecta App

Control your air conditioning with your phone through Daikin's own Onecta App. Available on Apple and Android, control your system with ease, from anywhere. Enjoy easy voice control of your units by connecting Onecta to Google Home or Amazon Alexa.

### Quiet by design

This unit is practically silent in operation — quieter than a soft whisper. It maintains the ideal indoor climate without interrupting your sleep, your thoughts, or your conversations, making it perfect for bedrooms, reading corners, and tranquil retail spaces alike.



FTXA-CW



FTXA-CB



FTXA-CS



RXA-A/B8



ARC466A85



WI-FI  
CONTROL  
VIA APP



WI-FI ADAPTOR

INCLUDED AS STANDARD



## FTXA-C (W/S/B) / RXA-A/B (8) stylish

**R-32** BLUEEVOLUTION

Indoor Units	White (RAL 9002)		CTXA15CW	FTXA20CW	FTXA25CW	FTXA35CW	FTXA42CW	FTXA50CW
	Black (RAL 9005)		CTXA15CB	FTXA20CB	FTXA25CB	FTXA35CB	FTXA42CB	FTXA50CB
	Silver (RAL 9006)		CTXA15CS	FTXA20CS	FTXA25CS	FTXA35CS	FTXA42CS	FTXA50CS
Capacity	UK Total Cooling	kW	Multi Combination Only	1.95	2.44	3.32	4.11	4.89
	UK Sensible Cooling	kW		1.95	1.96	2.43	3.01	3.56
	Nominal Cooling	kW		2.0	2.5	3.4	4.2	5.0
	Nominal Heating	kW		2.5	2.8	4.0	5.4	5.8
Seasonal Efficiency (EN14825) COOLING	Energy Label			A+++	A+++	A+++	A++	A++
	Pdesign	kW		2.0	2.5	3.4	4.2	5.0
	SEER			8.75	8.74	8.73	7.50	7.33
	Annual Energy Consumption	kWh		80	101	136	196	239
Seasonal Efficiency (EN14825) HEATING	Energy Label			A+++	A+++	A+++	A++	A++
	Pdesign	kW		2.40	2.45	2.50	3.80	4.00
	SCOP			5.15	5.15	5.15	4.6	4.6
	Annual Energy Consumption	kWh		652	666	680	1150	1217
Air Flow Rate (Cooling)	High / Med / Low / Silent	m <sup>3</sup> /min	11.0 / 8.2 / 6.1 / 4.6	11.0 / 8.2 / 6.1 / 4.6	11.5 / 8.6 / 6.1 / 4.6	11.9 / 8.6 / 6.1 / 4.6	13.1 / 9.8 / 7.2 / 4.6	13.5 / 10.4 / 7.6 / 5.2
Dimensions	Height / Width / Depth	mm	295 x 798 x 189	295 x 798 x 189	295 x 798 x 189	295 x 798 x 189	295 x 798 x 189	295 x 798 x 189
Weight		kg	12	12	12	12	12	12
Sound Pressure (Cooling)	High / Med / Low / Silent	dBA	39 / 32 / 25 / 21	39 / 32 / 25 / 19	40 / 33 / 25 / 19	41 / 33 / 25 / 19	45 / 37 / 29 / 21	46 / 39 / 31 / 24
Sound Power (Cooling)		dBA	57	57	57	60	60	60

Outdoor Units			Multi Combination Only	RXA20A8	RXA25A8	RXA35A8	RXA42B8	RXA50B8
Dimensions	Height x Width x Depth	mm		550 x 840 x 350	550 x 840 x 350	550 x 840 x 350	734 x 870 x 373	734 x 870 x 373
Weight		kg		32	32	32	50	50
Electrical Details	Power Supply			1ph	1ph	1ph	1ph	1ph
	Maximum Input Current (MCA)	A		9.88	11.17	12.29	12.8	12.8
	Max Fuse Size	A		10	13	13	16	16
Interconnection Wiring	Core / Cable Size			3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5	3+E / 1.5
Piping Connections	Liquid / Gas	inches (mm)		1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 1/2 (12.7)
Pipework	Maximum Length	m		20	20	20	30	30
	Maximum Vertical Rise	m		15	15	15	20	20
	Precharged to	m		10	10	10	10	10
	Additional charge	g/m		20	20	20	20	20
	Holding charge	kg		0.76	0.76	0.76	1.1	1.1
Sound Pressure (Cooling)	Nominal	dBA		46	46	49	48	48
Sound Power (Cooling)		dBA		59	59	61	62	62
Operating Range (Cooling)	Min / Max	°CDB		-10 / 46	-10 / 46	-10 / 46	-10 / 46	-10 / 46
Operating Range (Heating)	Min / Max	°CWB	-15 / 18	-15 / 18	-15 / 18	-15 / 18	-15 / 18	
Air Flow Rate (Cooling)	Nominal	m³/min	34.0	34.0	36.0	46.6	46.6	
Meets ETL criteria			●	●	●	●	●	

### Accessories:

Accessory Ref	Description
EKRS21	Wire harness for new S21 port for all marked (*) options
BRC073*	Wired remote control - connection cable required
BRCW901A03	3m extension cord required for wired remote controller BRC073
BRCW901A08	8m extension cord required for wired remote controller BRC073
K.CGM	Condensing unit guard (1150 x 1150 x 650)
K.CGS	Condensing unit guard (750 x 1050 x 460)
K.CWB90-2	Wall bracket (90kg, 500mm support arm)
K.DT1	Condensate drip tray for use with K.CWB90-2
K.FF600S	Two flexi-feet (Standard 600mm x 185mm x 100mm) to mount the outdoor unit
KLIC-DDV3*	KNX interface for Split type systems
KRP413A15*	Adaptor PCB for remote on/off control - constant/pulse contact
KRP928A25*	Adaptor PCB for interface to Daikin centralised control systems
RTD-RA*	Adaptor PCB for Modbus connection and/or extended system functions

### Notes & Features:

- › All fan coils are supplied with infrared remote controller ARC466A85
- › Fan with Coanda effect for optimum air distribution and indoor comfort
- › Grid eye sensor redirects air away from the occupants in the room
- › Flash Streamer technology helps improve indoor air quality
- › Antibacterial Filter for effectively arresting small particulates

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



FSC

Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)

**Daikin Airconditioning UK Limited** The Heights Brooklands Weybridge Surrey KT13 0NY Tel 01932 879000 [daikin.co.uk](http://daikin.co.uk)