



New design!

Ceiling mounted corner cassette

FXKA-A

1-way blow unit for corner installation

- Optimised design for R-32 refrigerant
- Compact dimensions enable installation in narrow ceiling void
- NEW** ▪ Modern decoration panel in white
- NEW** ▪ The air is comfortably spread up- and downwards thanks to 5 different discharge angles
- Optional fresh air intake
- Standard drain pump increases the reliability of the drain system



 2.2 kW
  7.1 kW
 2.5 kW
  8.0 kW

FXKA-A

Unique flap design



FXKA-A



Indoor Unit				FXKA	20A	25A	32A	40A	50A	63A
Cooling capacity	Total capacity	At high fan speed		kW	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Total capacity	At high fan speed		kW	2.5	3.2	4	5	6.3	8
Power input - 50Hz	Cooling	At high fan speed		kW	0.026		0.039	0.047	0.073	0.118
	Heating	At high fan speed		kW	0.034		0.039	0.047	0.073	0.118
Required ceiling void >				mm	260					
Dimensions	Unit	HeightxWidthxDepth		mm	200 x840 x470				200 x1,240 x470	
Weight	Unit			kg	18		19	24		
Casing	Material				Galvanised steel					
Decoration panel	Model				BYK32GJW1				BYK63GJW1	
	Colour				Fresh White					
	Dimensions	HeightxWidthxDepth		mm	80 x950 x550				80 x1,350 x550	
	Weight			kg	8				10	
Fan	Air flow rate - 50Hz	Cooling	At high fan speed / At medium fan speed / At low fan speed	m³/min	7.5 / 6.3 / 5		9.4 / 8.5 / 7.6	14.4 / 12.6 / 11.1	17.6 / 14.4 / 12.6	21.5 / 17.6 / 14.4
		Heating	At high fan speed / At medium fan speed / At low fan speed	m³/min	8.6 / 7.3 / 5.8		9.4 / 8.5 / 7.6	14.4 / 12.6 / 11.1	17.6 / 14.4 / 12.6	21.5 / 17.6 / 14.4
Air filter		Type			Removable / washable					
Sound power level	Cooling	At high fan speed / At medium fan speed / At low fan speed		dBA	46 / 43.5 / 41		50.5 / 48.5 / 46.5	52.5 / 50 / 48	57 / 52.5 / 50	61.5 / 57 / 52.5
Sound pressure level	Cooling	At high fan speed / At medium fan speed / At low fan speed		dBA	32 / 27.5 / 22.5		37 / 34 / 31.5	38.5 / 34.5 / 31.5	42 / 38 / 34.5	48.5 / 43.5 / 38.5
	Heating	At high fan speed / At medium fan speed / At low fan speed		dBA	36 / 31 / 25.5		39 / 35.5 / 32.5	39.5 / 36 / 32.5	44 / 39.5 / 36	49 / 44 / 39.5
Refrigerant	Type/GWP				R-32/675					
Piping connections	Liquid	OD		mm	6.4					
	Gas	OD		mm	9.5				12.7	
	Drain				I.D. 20/O.D. 26					
Power supply	Phase/Frequency/Voltage				1~/50/60/220-240/220					
Current - 50Hz	Maximum fuse amps (MFA)				6					
Control systems	Wired remote control				BRC1H52W/S/K / BRC1H82W/S/K					

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Publisher)



FSC label

Printed on non-chlorinated paper.
ECPEN24-241 06/2024



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.